




The world's leading supplier of broadband power amplifiers.


Model #: SM-915-3E2 Frequency Range: 915 ± 1 MHz

### Specifications\*

Printer Friendly Version



Operating frequency	915 ± 1 MHz
CW power	0-300 W (min.)
Harmonic content (2nd/3rd)	-20 dB/ -12 dBc, typ.
Output impedance	50 ohms (nominal)



#### Communication Power Corporation

80 Davids Drive, Suite 3  
 Hauppauge, New York 11788  
 Phone: 631. 434. 7306 Fax: 631. 434. 7026  
 email: info@cpcamps.com  
 Web Site: www.CPCAMPS.COM



\* CPC reserves the right to change specifications without notice.



The world's leading supplier of broadband power amplifiers.

Model #: SM-915-3E2 Frequency Range: 915 ± 1 MHz

## System Features



### Protection functions:

- Auto/manual fault reset
- Maximum output power
- Over temperature
- Power supply over voltage

### Controls, front panel:

- AC power on/off
- Forward/ Reflected RF Power
- Fault reset

### Connectors, rear panel:

- AC mains, Receptacles, EMI filtered
- RF output: Type N (F)
- Interface: 25 pin D (F), EMI filtered
- Fwd/ Ref RF sample: SMA (F)
- Protective ground: threaded bolt

### Front panel indicators:

- AC power on
- Standby mode
- Thermal fault
- Power supply status

### Interface functions:

- (C= Control Input F= Flag Output)
- Thermal (F)
- Power supply (F)
- Standby (C/F)
- RF overdrive (F)

### Communication Power Corporation

80 Davids Drive, Suite 3  
Hauppauge, New York 11788  
Phone: 631.434.7306 Fax: 631.434.7026  
email: info@cpcamps.com  
Web Site: www.CPCAMPS.COM

\* CPC reserves the right to change specifications without notice.





The world's leading supplier of broadband power amplifiers.

Model #: SM-915-3E2 Frequency Range: 915 ± 1 MHz



### Environmental

Cooling	Internal forced air, front to back flow
Operating temperature	+10 to 40°C
AC line voltage	208 VAC, +/- 10%, 47-63 Hz
Chassis size	8.75 x 19 x 26 (HWD, inches) Rack mountable
Net weight	80 lbs. (approx.)
Compliance	CE, UL 2601 upon request



#### Communication Power Corporation

80 Davids Drive, Suite 3  
Hauppauge, New York 11788  
Phone: 631. 434. 7306 Fax: 631. 434. 7026  
email: info@cpcamps.com  
Web Site: www.CPCAMPS.COM

\* CPC reserves the right to change specifications without notice.